Office of Naval Research Contract Nonr-610 (06)
Task Order NR 064-476

AD 639501

Technical Report No. 3

GEOMETRIC DISCONTINUITIES IN ELASTOSTATICS

CLEARINGHOUSE
FOR FEDERAL SCIENTIFIC AND
TECHNICAL INFORMATION
Hardcopy | Microfiche | 32 pp
$3.00 | $0.50
ARCHIVE COPY
code 1

DDC
RECEIVED
OCT 5 1966
C

by
M. K. Kassir
G. C. Sih

June 1966

Department of Applied Mechanics
Lehigh University, Bethlehem, Pennsylvania

LEHIGH UNIVERSITY INSTITUTE OF RESEARCH

Office of Naval Research

Contract Nonr-610(06)

Task Order NR 064-476

Technical Report No. 3

GEOMETRIC DISCONTINUITIES IN ELASTOSTATICS

by

M. K. Kassir and G. C. Sih

Department of Applied Mechanics
Lehigh University
Bethlehem, Pennsylvania

June 1966

Reproduction in whole or in part is permitted by the United States Government. Distribution of this document is unlimited.

GEOMETRIC DISCONTINUITIES IN ELASTOSTATICS[1]

by

M. K. Kassir[2] and G. C. Sih[3]

Abstract. Three-dimensional elastostatic problems for an infinite solid with geometric discontinuities are formulated and solved with the aid of potential functions. In the problem of a linearly varying pressure specified over a plane region bounded by an ellipse, use is made of the gravitational potential at an exterior point of a homogeneous elliptical disk. The problem of prescribing displacements on the surfaces of discontinuity is governed by the Newtonian potential of a simple layer distributed over a disk in the shape of the region of discontinuity. The mass density of the disk is proportional to the prescribed normal displacement. For an "elliptically-shaped" region, the application of the symmetrical form of ellipsoidal coordinates leads to an integral equation of the Abel type for the potential function. It is shown that if the displacements normal to the elliptical plane are given by $(1 - \frac{x^2}{a^2} - \frac{y^2}{b^2})^{n} Q_n(x^2,y^2)$, where $Q_n(x^2,y^2)$ is a polynomial of degree n in x^2 and y^2, then the corresponding normal stress acting over the ellipse is also a polynomial, $P_n(x^2,y^2)$, of the same degree in x^2 and y^2. In the case of a circular region of discontinuity, the solution can be carried out for any arbitrary value of n. The results are useful in the prediction of the stability behavior of elastic solids containing geometric discontinuities.

---

[1]The work reported in this paper was carried out under Contract Nonr-610(06) with the Office of Naval Research, U. S. Navy.

[2]Instructor of Mechanics, Lehigh University, Bethlehem, Pa.

[3]Professor of Mechanics, Lehigh University, Bethlehem, Pa.

1. Introduction. The rediatribution of atresses due to the presence of geometric diacontinuities in elastic aolida has been the aubject of many past discussions. Among the three-dimenaional problems conaidered previously, the majority of them pertains to geometriea end applied loadinga that possesa exial symmetry. A collection of previous work can be found in the notes of Sneddon [1] and the referencea therein. The non-symmetric problems involving geometric discontinuities are more difficult and have been inveatigated only in a limited number of special caaea.

A knowledge of the clessicel potential theory is pertinent to the formulation of boundary value problems with planes of discontinuities in the three-dimensional space. For definiteness sake, the region of discontinuity will be assumed to take the form of a plane ellipse described by

$$\frac{x^2}{a^2} + \frac{y^2}{b^2} = 1 \quad , \quad z = 0, \tag{1.1}$$

which is referred to a set of cartesian coordinates x, y, and z. The major and minor semi-axes of the ellipse are denoted by a and b, respectively. If pressures, p(x,y), are applied symmetrically to the upper and lower sides of the elliptical plane, the problem reduces to the determination of a aingle harmonic function [2], f(x,y,z), setiafying the boundary conditiona

$$\frac{\partial^2 f}{\partial z^2} = -\frac{p(x,y)}{2\mu} \quad , \quad \left(\frac{x^2}{a^2} + \frac{y^2}{b^2} < 1, \; z = 0\right) \tag{1.2}$$

$$\frac{\partial f}{\partial z} = 0 \, , \qquad \left(\frac{x^2}{a^2} + \frac{y^2}{b^2} > 1, \; z = 0\right) \tag{1.3}$$

where μ is the sheer modulus of the elastic solid. Since f(x,y,z) is harmonic, theae conditiona mey be expreesed in the equivalent form

$$f = p^*(x,y) \quad , \qquad \left(\frac{x^2}{a^2} + \frac{y^2}{b^2} < 1, \; z = 0\right) \tag{1.4}$$

$$\frac{\partial f}{\partial z} = 0 \quad , \quad \left(\frac{x^2}{a^2} + \frac{y^2}{b^2} > 1, \; z = 0\right) \tag{1.5}$$

and $p^*(x,y)$ is a particular solution of the Poisson equation in two-dimensions

$$\frac{\partial^2 p^*}{\partial x^2} + \frac{\partial^2 p^*}{\partial y^2} = \frac{p(x,y)}{2\mu} \tag{1.6}$$

The problem is to determine the potential function $f(x,y,z)$ such that it satisfies (1.4) and (1.5).

Green and Sneddon [3] have examined the problem of a flat elliptical discontinuity opened by a uniform pressure, $p(x,y)$ = constant. In part of the work to follow, $p(x,y)$ is taken to be a linear function of x and/or y, i.e.,

$$p(x,y) = C_1 + C_2 x + C_3 y . \tag{1.7}$$

where c_j (j=1,2,3) are constants related to the intensity of the applied pressure. An exact solution is given for the case of $c_1 = c_3 = 0$ and $c_2 = -p_0/2\mu$. The same method of solution may be used for $c_1 = c_2 = 0$ and $c_3 = -p_0/2\mu$. An attempt has also been made to find $f(x,y,z)$ corresponding to a general expression of $p(x,y)$, say

$$p(x,y) = \sum_{n=0}^{m} \left(A_n x^{2n} + B_n y^{2n}\right) \tag{1.8}$$

The end results appear to be rather restricted in the sense that the coefficients A_n, B_n of the polynomial $p(x,y)$ are required to depend upon each other.

An alternative formulation of the problem is to determine the distribution of pressure necessary to preserve certain shape of the surfaces of discontinuity. This can be accomplished by specifying equal and opposite normal displacements, $q(x,y)$, on the region given by (1.1). For this class of problems, the boundary conditions are

$$\frac{\partial f}{\partial z} = -\frac{q(x,y)}{2(1-\nu)} \quad , \quad \left(\frac{x^2}{a^2} + \frac{y^2}{b^2} < 1, \; z = 0\right) \tag{1.9}$$

$$\frac{\partial f}{\partial z} = 0 \quad , \qquad \left(\frac{x^2}{a^2} + \frac{y^2}{b^2} > 1,\ z = 0\right) \tag{1.10}$$

where ν is Poisson's ratio. Equations (1.9) and (1.10) show that f(x,y,z) is equivalent to the potential of a simple layer distributed over an elliptical disk. The mass density of the disk is proportional to q(x,y). For this reason, solutions of considerably general in nature may be found. In fact, if the normal displacements are given by a polynomial q(x,y) of degree n in x^2 and y^2, then the integrals representing f(x,y,z) can be evaluated in closed form. The only limitation for the elliptical geometry is that the degree of q(x,y) must be equal to m+½, m being a positive integer. The circular region problem, however, is free from such a restriction.

The problem of specifying pressures and/or displacements, equal in magnitude but opposite in sign, to the planes of a flat ellipse may also be formulated. Kassir and Sih [4] have shown that the the skew-symmetric problem requires the knowledge of two harmonic functions g(x,y,z) and h(x,y,z). The simple case of an elliptically-shaped plane of discontinuity, whose surfaces are subjected to uniform shear, was discussed in [4]. Without further comments, it is obvious that a general treatment of the skew-symmetric problem follows immediately from the work presented in this paper and in [4].

2. Equations in Elastostatics. Consider the problem of finding stresses and displacements in an infinite elastic solid whose continuity is interrupted by a void in the shape of a plane ellipse. The applied pressures or displacements on the upper surface of this ellipse are equal to those on the lower surface. Hence, the problem is said to be symmetric with respect to the elliptical region located, say at z = o or in the xy-plane. Outside of this region, the shear stresses τ_{xz} and τ_{yz} must vanish at z = o. These conditions may be satisfied by expressing the cartesian components u, v, and w of the

displacement vector in terms of a single harmonic function f(x,y,z) as

$$u = (1-2\nu)\frac{\partial f}{\partial x} + z\frac{\partial^2 f}{\partial x \partial z}, \tag{2.1}$$

$$v = (1-2\nu)\frac{\partial f}{\partial y} + z\frac{\partial^2 f}{\partial y \partial z}, \tag{2.2}$$

$$w = -2(1-\nu)\frac{\partial f}{\partial z} + z\frac{\partial^2 f}{\partial z^2}. \tag{2.3}$$

The details are omitted here since they have already been given elsewhere [2]. In the usual way, the stress components τ_{xz}, τ_{yz}, and σ_{zz} are given by

$$\tau_{xz} = 2\mu z\frac{\partial^3 f}{\partial x \partial z^2}, \tag{2.4}$$

$$\tau_{yz} = 2\mu z\frac{\partial^3 f}{\partial y \partial z^2}, \tag{2.5}$$

$$\sigma_{zz} = 2\mu\left(-\frac{\partial^2 f}{\partial z^2} + z\frac{\partial^3 f}{\partial z^3}\right). \tag{2.6}$$

For the mere purpose of determining the potential function f(x,y,z), the remaining stress components σ_{xx}, σ_{yy}, and τ_{xy} are not needed.

3. Linearly Varying Pressure. Let the two sides of the elliptical plane of discontinuity be subjected to a pressure that varies linearly with the coordinate x over the region in (1.1). The disturbance of the discontinuity diminishes at large distance away from the origin. On the plane z = 0, (2.3) and (2.6) yield

$$\frac{\partial^2 f}{\partial z^2} = -\frac{p_0 x}{2\mu}, \qquad \left(\frac{x^2}{a^2} + \frac{y^2}{b^2} < 1,\ z = 0\right) \tag{3.1}$$

$$\frac{\partial f}{\partial z} = 0, \qquad \left(\frac{x^2}{a^2} + \frac{y^2}{b^2} > 1,\ z = 0\right) \tag{3.2}$$

It is assumed here that the second and third derivatives of f(x,y,z) with respect to z are bounded in the limit as z approaches zero. These requirements will be met in the subsequent analysis.

The problem can be readily solved upon defining a new harmonic function $\phi(x,y,z)$ related to $f(x,y,z)$ by

$$\frac{\partial f}{\partial z} = x\frac{\partial \phi}{\partial z} - z\frac{\partial \phi}{\partial x}\ , \tag{3.3}$$

where

$$\nabla^2 f(x,y,z) = 0\ , \qquad \nabla^2 \phi(x,y,z) = 0$$

and ∇^2 is the Laplacian operator in three dimensions. From (3.3), it can be shown that

$$\frac{\partial f}{\partial x} = \frac{\partial}{\partial x}(x\phi) + \int_z^\infty z\frac{\partial^2 \phi}{\partial x^2}\,dz\ , \tag{3.4}$$

$$\frac{\partial f}{\partial y} = \frac{\partial}{\partial y}(x\phi) + \int_z^\infty z\frac{\partial^2 \phi}{\partial y \partial x}\,dz\ . \tag{3.5}$$

The limits of the integrals in (3.4) and (3.5) are introduced in such a way that the stresses and displacements vanish as z goes to infinity. In terms of the function $\phi(x,y,z)$, the displacements become

$$u = (1-2\nu)\frac{\partial}{\partial x}\left[x\phi + \int_z^\infty z\frac{\partial \phi}{\partial x}\,dz\right] + z\frac{\partial^2}{\partial x \partial z}\left[x\phi + \int_z^\infty z\frac{\partial \phi}{\partial x}\,dz\right], \tag{3.6}$$

$$v = (1-2\nu)\frac{\partial}{\partial y}\left[x\phi + \int_z^\infty z\frac{\partial \phi}{\partial x}\,dz\right] + z\frac{\partial^2}{\partial y \partial z}\left[x\phi + \int_z^\infty z\frac{\partial \phi}{\partial x}\,dz\right], \tag{3.7}$$

$$w = -2(1-\nu)\left[x\frac{\partial \phi}{\partial z} - z\frac{\partial \phi}{\partial x}\right] + z\frac{\partial}{\partial z}\left[x\frac{\partial \phi}{\partial z} - z\frac{\partial \phi}{\partial x}\right]. \tag{3.8}$$

Using (3.3)-(3.5), the stress components are

$$\tau_{xz} = 2\mu z\frac{\partial^2}{\partial x \partial z}\left(x\frac{\partial \phi}{\partial z} - z\frac{\partial \phi}{\partial x}\right), \tag{3.9}$$

$$\tau_{yz} = 2\mu z\frac{\partial^2}{\partial y \partial z}\left(x\frac{\partial \phi}{\partial z} - z\frac{\partial \phi}{\partial x}\right), \tag{3.10}$$

$$\sigma_{zz} = 2\mu\left[\frac{\partial \phi}{\partial x} - x\frac{\partial^2 \phi}{\partial z^2} + z\frac{\partial}{\partial z}\left(x\frac{\partial^2 \phi}{\partial z^2} - z\frac{\partial^2 \phi}{\partial x \partial z}\right)\right], \tag{3.11}$$

Thus, the boundary conditions (3.1) and (3.2) take the form

$$\frac{\partial \phi}{\partial x} - x \frac{\partial^2 \phi}{\partial z^2} = \frac{p_0 x}{2\mu}, \quad \left(\frac{x^2}{a^2} + \frac{y^2}{b^2} < 1, z = 0\right) \tag{3.12}$$

$$x \frac{\partial \phi}{\partial z} - z \frac{\partial \phi}{\partial x} = 0, \quad \left(\frac{x^2}{a^2} + \frac{y^2}{b^2} > 1, z = 0\right) \tag{3.13}$$

Upon introducing a system of ellipsoidal coordinates, the position of a point can be determined by the three parameters ξ, η, ζ, the limits of variation of which are

$$\infty > \xi \geq 0 \geq \eta \geq -b^2 \geq \zeta \geq -a^2. \tag{3.14}$$

The cartesian coordinates x,y,z may be expressed in terms of these parameters by the relations

$$a^2(a^2 - b^2) x^2 = (a^2 + \xi)(a^2 + \eta)(a^2 + \zeta), \tag{3.15}$$

$$b^2(b^2 - a^2) y^2 = (b^2 + \xi)(b^2 + \eta)(b^2 + \zeta), \tag{3.16}$$

$$a^2 b^2 z^2 = \xi \eta \zeta. \tag{3.17}$$

In the plane z = 0, the inside of the ellipse $x^2/a^2 + y^2/b^2 = 1$ may be distinguished from the outside by setting $\xi = 0$ and $\eta = 0$, respectively. The boundary of the ellipse is identified by $\xi = \eta = 0$.

Since the function $\phi(x,y,z)$ is equivalent to the gravitational potential of a homogeneous elliptical disk at an exterior point x,y,z, the solution is given by [5]

$$\phi(x,y,z) = \frac{A}{2} \int_{\xi}^{\infty} \left[\frac{x^2}{a^2+s} + \frac{y^2}{b^2+s} + \frac{z^2}{s} - 1\right] \frac{ds}{\sqrt{Q(s)}}, \tag{3.18}$$

where

$$Q(s) = s(a^2+s)(b^2+s). \tag{3.19}$$

Inserting (3.18) into (3.12) and (3.13), the constant A is found to be

$$A = \left(\frac{p_0 a^3}{4\mu}\right) \cdot \frac{k^2 k'^2}{k'^2 K(k) - E(k)}. \tag{3.20}$$

In (3.20), K(k) and E(k) are Legendre's complete elliptic integrals of the

first and second kind, respectively, for the modulus

$$k^2 = 1 - \left(\frac{b}{a}\right)^2,$$

and $k'^2 = 1 - k^2$. Once $\phi(x,y,z)$ is known, the stresses and displacements at any point of the solid can be calculated in a straightforward manner.

For instance, the displacements u, v, and w in the plane z = 0 may be obtained readily from (3.6)-(3.8) which reduce to

$$u = (1-2\nu)\frac{\partial}{\partial x}\left(x\phi + \frac{\partial \psi}{\partial x}\right), \tag{3.21}$$

$$v = (1-2\nu)\frac{\partial}{\partial y}\left(x\phi + \frac{\partial \psi}{\partial x}\right), \tag{3.22}$$

$$w = -2(1-\nu)\, x\frac{\partial \phi}{\partial z}. \tag{3.23}$$

in which

$$\psi(x,y,z) = \int_z^\infty z\,\phi(x,y,z)\,dz. \tag{3.24}$$

Introducing the contraction

$$\omega(s) = 1 - \frac{x^2}{a^2+s} - \frac{y^2}{b^2+s} - \frac{z^2}{s}, \tag{3.25}$$

and substituting (3.18) into (3.24), the function $\psi(x,y,z)$ may be represented by the integral

$$\psi(x,y,z) = -\frac{A}{2}\int_z^\infty z\left[\int_\xi^\infty \omega(s)\frac{ds}{\sqrt{Q(s)}}\right]dz \tag{3.26}$$

$$= -\frac{A}{8}\int_\xi^\infty [\omega(s)]^2 \frac{s\,ds}{\sqrt{Q(s)}}.$$

It follows that

$$\frac{\partial^2 \psi}{\partial x^2} = \frac{A}{2}\int_\xi^\infty \omega(s)\cdot\frac{s\,ds}{(a^2+s)\sqrt{Q(s)}} - Ax^2\int_\xi^\infty \frac{s\,ds}{(a^2+s)^2\sqrt{Q(s)}}, \tag{3.27}$$

$$\frac{\partial^2 \psi}{\partial x\,\partial y} = -Axy\int_\xi^\infty \frac{s\,ds}{(a^2+s)(b^2+s)\sqrt{Q(s)}}. \tag{3.28}$$

The results of putting (3.18), (3.27), and (3.28) into (3.21)-(3.23) are

$$u = (1-2\nu)\cdot\frac{Aa^2}{2}\left[3x^2\int_\xi^\infty \frac{ds}{(a^2+s)^2\sqrt{Q(s)}} + y^2\int_\xi^\infty \frac{ds}{(a^2+s)(b^2+s)\sqrt{Q(s)}} - \int_\xi^\infty \frac{ds}{(a^2+s)\sqrt{Q(s)}}\right], \quad (3.29)$$

$$v = (1-2\nu)\cdot A a^2 x y \int_\xi^\infty \frac{ds}{(a^2+s)(b^2+s)\sqrt{Q(s)}}, \quad (3.30)$$

$$w = -2(1-\nu)Ax \lim_{z\to 0}\left[z\int_\xi^\infty \frac{ds}{s\sqrt{Q(s)}}\right]. \quad (3.31)$$

The integrals in (3.29)-(3.31) may be evaluated in closed form. They are

$$\int_\xi^\infty \frac{ds}{(a^2+s)\sqrt{Q(s)}} = \frac{2}{a^3k^2}\left[u - E(u)\right], \quad (3.32)$$

$$\int_\xi^\infty \frac{ds}{(b^2+s)\sqrt{Q(s)}} = \frac{2}{a^3k^2k'^2}\left[E(u) - k'^2u - k^2\frac{\mathrm{sn}\,u\,\mathrm{cn}\,u}{\mathrm{dn}\,u}\right], \quad (3.33)$$

and others of the same type. The quantity E(u) is

$$E(u) = \int_0^u \mathrm{dn}^2 t\,dt, \quad (3.34)$$

and snu, cnu, dnu are the Jacobian elliptic functions whose variable u should be distinguished from the x-component of the displacement vector. Here u is related to the ellipsoidal coordinate ξ by

$$\xi = a^2\,\mathrm{cn}^2u/\mathrm{sn}^2u = a^2(\mathrm{sn}^{-2}u - 1). \quad (3.35)$$

After some manipulations, the displacements for z = 0 are

$$u = \frac{(1-2\nu)A}{a^3k^2}\left\{x^2\left[\left(1+\frac{2}{k^2}\right)u - 2\left(1+\frac{1}{k^2}\right)E(u) + \mathrm{sn}\,u\,\mathrm{cn}\,u\,\mathrm{dn}\,u\right]\right.$$

$$\left. - y^2\left[\frac{2}{k^2}u - \frac{1+k'^2}{k^2k'^2}E(u) + \frac{1}{k'^2}\mathrm{sn}\,u\,\mathrm{cn}\,u/\mathrm{dn}\,u\right] + a^2\left[E(u)-u\right]\right\}, \quad (3.36)$$

$$v = \frac{(1-2\nu)A}{a^3k^2}\cdot xy\left[\left(1+\frac{1}{k'^2}\right)E(u) - 2u - \frac{k^2}{k'^2}\frac{\mathrm{sn}\,u\,\mathrm{cn}\,u}{\mathrm{dn}\,u}\right], \quad (3.37)$$

$$w = -\frac{4(1-\nu)A}{ab^2}\,x \lim_{z\to 0} z\left[\frac{\mathrm{sn}u\,\mathrm{dn}u}{\mathrm{cn}u} - E(u)\right]. \tag{3.38}$$

On the plane surface of the discontinuity, i.e., for $\xi = 0$, (3.36)-(3.38) may be simplified since

$$E(u)\to E(k)\ ,\quad u\to K(k)\ ,\quad \frac{\mathrm{sn}u\,\mathrm{cn}u}{\mathrm{dn}u}\to 0\ ,\quad \text{as}\quad \xi\to 0.$$

Hence, the deformed shape of the ellipse $x^2/a^2+y^2/b^2 = 1$ is given by

$$(u)_{\xi=0} = \frac{(1-2\nu)A}{a^3k^4}\Big\{x^2\left[(2+k^2)K(k) - 2(1+k^2)E(k)\right] - y^2\left[2K(k) - (1+\tfrac{1}{k'^2})E(k)\right] + a^2k^2\left[E(k)-K(k)\right]\Big\}, \tag{3.39}$$

$$(v)_{\xi=0} = \frac{2(1-2\nu)A}{a^3k^4}\cdot xy\left[(1+\tfrac{1}{k'^2})E(k) - 2K(k)\right], \tag{3.40}$$

$$(w)_{\xi=0} = -\frac{4(1-\nu)Ax}{ab}\left(1-\frac{x^2}{a^2}-\frac{y^2}{b^2}\right)^{\frac{1}{2}}. \tag{3.41}$$

The constant A has already been determined in (3.20).

Of interest is the intensification of the normal stress σ_{zz} in the neighborhood of the geometric discontinuity. It is the local elevation of σ_{zz} in the vicinity of the edge of the discontinuity ($\xi\to 0, \eta\to 0$) that controls the stability behavior [4] of the plane elliptical cavity. From (3.11)

$$\sigma_{zz} = 2\mu\left(\frac{\partial\phi}{\partial x} - x\frac{\partial^2\phi}{\partial z^2}\right),\quad z=0 \tag{3.42}$$

Inserting (3.18) into (3.42) and integrating, the obtained result gives

$$(\sigma_{zz})_{\eta=0} = \frac{2Ax}{a^3k^2}\left\{u - E(u) - \frac{a^3k^2}{\sqrt{Q(\xi)}} - \left(1-\frac{a^2}{b^2}\right)\left[E(u) - \frac{\mathrm{sn}u\,\mathrm{cn}u}{\mathrm{dn}u}\right]\right\}_{\eta=0} \tag{3.43}$$

The expression (3.43) is valid only in the region outside of the ellipse $x^2/a^2+y^2/b^2 = 1$. To find σ_{zz} near the periphery of the elliptical boundary, the asymptotic value of ξ is required. By taking a vector $\underset{\sim}{\rho}$ normal to the curve that defines the ellipse with parametric equations

$$x = a\sin\phi \quad , \quad y = b\cos\phi \tag{3.44}$$

the expansion

$$\xi = \frac{2ab\rho}{(a^2\sin^2\phi + b^2\cos^2\phi)^{1/2}} + \cdots \tag{3.45}$$

is obtained for which terms of order higher than ρ have been neglected since ρ , the magnitude of $\underset{\sim}{\rho}$, has been assumed to be small in comparison with either a or b. In addition, it can be shown that

$$\zeta = -(a^2\sin^2\phi + b^2\cos^2\phi) \tag{3.46}$$

The limiting forms of ξ and ζ lead to

$$(\sigma_{zz})_{\eta=0} = -\frac{4\mu}{a^{1/2}b^{3/2}}\frac{A}{\sqrt{2\rho}}(a^2\sin^2\phi + b^2\cos^2\phi)^{\frac{1}{4}}\cos\phi + \cdots \quad , \quad \xi \to 0 \tag{3.47}$$

Denoting the coefficient of $1/\sqrt{2\rho}$ by k_1 and using (3.20) yield

$$k_1 = \frac{p_0 k^2 (ab)^{1/2}}{E(k) - k'^2 K(k)}(a^2\sin^2\phi + b^2\cos^2\phi)^{\frac{1}{4}}\cos\phi \tag{3.48}$$

This is known as the three-dimensional "stress-intensity factor" [4] the critical value of which governs the onset of unstable motion of the geometric discontinuity under consideration.

The applied pressure on the ellipse $x^2/a^2+y^2/b^2 = 1$ may also depend on x^{2n}, y^{2n}, where n is a positive integer. For n = 1, the function

$$f(x,y,z) = \frac{B}{2}\int_{\xi}^{\infty}[\omega(s)]^2\frac{ds}{\sqrt{Q(s)}} \tag{3.49}$$

will satisfy the boundary conditions

$$\frac{\partial^2 f}{\partial z^2} = \frac{4B}{a^5k^2}\left\{\frac{a^4k^2}{b^2}E(k) - \left[\left(\frac{k^2}{k'^2}-1\right)E(k) + K(k)\right]x^2 - \right. \tag{3.50}$$

$$-\frac{1}{k'^2}\left[\left(\frac{k^2+1}{k'^2}\right)E(k)-K(k)\right]y^2\Big\}\,,\quad \xi=0$$

$$\frac{\partial f}{\partial z}=0\,,\qquad \eta=0 \tag{3.51}$$

However, the reault baaed on (3.49) will obviously be limited to the type of preasure diatribution aa indicated in (3.50). Similar obaervationa may be made for n greater than one.

4. Specification of Displacements. As mentioned earlier, when the region of discontinuity undergoes certain normal displacements, q(x,y), that are preacribed, the problem can in general be solved for the diatribution of the normal pressure which is initially unknown. The conditions (1.9) and (1.10) suggest taking the function f(x,y,z) as the Newtonian potential of a simple layer of intensity q(x,y) diatributed over the plane region Ω in the shape of the ellipse $x^2/a^2+y^2/b^2 = 1$. The potential is

$$f(x,y,z)=\frac{1}{4\pi(1-\nu)}\iint_{\Omega}\frac{q(X,Y)}{R}\,dX\,dY\,, \tag{4.1}$$

where R denotes

$$R=\left[(x-X)^2+(y-Y)^2+z^2\right]^{1/2}.$$

The function f(x,y,z) ia harmonic and ia continuous in the entire three-dimensional region excluding Ω. Furthermore, it vanishea for distances sufficiently far away from Ω since

$$f\to\frac{1}{R}\left[\frac{1}{4\pi(1-\nu)}\iint_{\Omega}q(X,Y)\,dX\,dY\right]\,,\quad \text{as}\quad R\to\infty$$

The normal derivative of f(x,y,z) ia diacontinuous for the transition from one side of Ω, say $z = 0^+$, to the other, $z = 0^-$, i.e.,

$$\left(\frac{\partial f}{\partial z}\right)_{z\to 0^{\pm}}=\begin{cases}\mp\dfrac{q(x,y)}{2(1-\nu)}\,, & \xi=0 \qquad (4.2)\\[2ex] 0\,, & \eta=0 \qquad (4.3)\end{cases}$$

Hence, (1.9) and (1.10) are satisfied automatically when f(x,y,z) is constructed from the potential of a simple layer.

For the present problem, it is more convenient to employ the symmetrical form of ellipsoidal coordinates ξ, η, ζ as given in (3.14)-(3.17). Proposed as a possible solution is the function [6]

$$f(x,y,z) = \int_{\xi}^{\infty} \lambda(\omega) \frac{ds}{\sqrt{Q(s)}} \tag{4.4}$$

The variable ω is defined by (3.25) or the equivalent form

$$\omega(s) = \frac{(s-\xi)(s-\eta)(s-\zeta)}{Q(s)}$$

and λ is a twice differentiable function in the interval (0,1) with finite one-sided derivatives at the boundary points of the interval. Differentiating (4.4) with respect to x renders

$$\frac{\partial f}{\partial x} = \int_{\xi}^{\infty} \frac{\partial \lambda(\omega)}{\partial x} \frac{ds}{\sqrt{Q(s)}} + \lambda(0) \frac{\partial I_0(\xi)}{\partial x}, \tag{4.5}$$

$$\frac{\partial^2 f}{\partial x^2} = \int_{\xi}^{\infty} \frac{\partial^2 \lambda(\omega)}{\partial x^2} \frac{ds}{\sqrt{Q(s)}} + 4 \frac{\lambda'(0)}{\sqrt{Q(\xi)}} \frac{\partial x}{\partial \xi} \frac{\partial \xi}{\partial x} + \lambda(0) \frac{\partial^2 I_0(\xi)}{\partial x^2}, \tag{4.6}$$

in which

$$I_0(\xi) = \int_{\xi}^{\infty} \frac{ds}{\sqrt{Q(s)}},$$

satisfies the harmonic equation $\nabla^2 I_0 = 0$. The remaining expressions of $\partial f/\partial y$, $\partial^2 f/\partial y^2$, and $\partial f/\partial z$, $\partial^2 f/\partial z^2$, may be obtained simply by permutation of the variable x in (4.5), (4.6) to y and z, respectively. As a result, the Laplacian of f(x,y,z) can be written as

$$\nabla^2 f(x,y,z) = \int_{\xi}^{\infty} \nabla^2 \lambda(\omega) \frac{ds}{\sqrt{Q(s)}} + 4 \frac{\lambda'(0)}{\sqrt{Q(\xi)}}, \tag{4.7}$$

with the knowledge that [7]

$$\frac{\partial x}{\partial \xi} \frac{\partial \xi}{\partial x} + \frac{\partial y}{\partial \xi} \frac{\partial \xi}{\partial y} + \frac{\partial z}{\partial \xi} \frac{\partial \xi}{\partial z} = 1.$$

Now, computing the derivatives

$$\frac{\partial \lambda(\omega)}{\partial x} = -\frac{2x}{a^2+s}\lambda'(\omega),$$

$$\frac{\partial^2 \lambda(\omega)}{\partial x^2} = -\frac{2}{a^2+s}\left[\lambda'(\omega) - \frac{2x^2}{a^2+s}\lambda''(\omega)\right],$$

and etc., the integrand, $\nabla^2\lambda(\omega)$, in (4.7) becomes

$$\nabla^2\lambda(\omega) = -\frac{2Q'(s)}{Q(s)}\lambda'(\omega) + 4\omega'(s)\lambda''(\omega) = 4\sqrt{Q(s)}\,\frac{d}{ds}\left[\frac{\lambda'(\omega)}{\sqrt{Q(s)}}\right]. \tag{4.8}$$

By means of (4.7) and (4.8), f(x,y,z) is indeed a solution of the equation

$$\nabla^2 f(x,y,z) = 0.$$

There remains the determination of $\lambda(\omega)$ which may be evaluated from the boundary conditions (4.2) and (4.4). First of all, replacing x by z in (4.5) and using the relation

$$\frac{\partial \xi}{\partial z} = \frac{2z\,Q(\xi)}{\xi(\xi-\eta)(\xi-\zeta)},$$

the result is

$$\frac{\partial f}{\partial z} = -2\frac{(\xi\eta\zeta)^{\frac{1}{2}}}{ab}\int_{\xi}^{\infty}\lambda'(\omega)\frac{ds}{s\sqrt{Q(s)}} - 2\lambda(0)\frac{[\eta\zeta(a^2+\xi)(b^2+\xi)]^{\frac{1}{2}}}{ab(\xi-\eta)(\xi-\zeta)}. \tag{4.9}$$

While (4.9) satisfies (4.3) for $\eta = 0$, it reduces to an integral equation of the Abel type for $\xi = 0$ as dictated by (4.2). This will be shown in the next section.

5. The Abel Integral. Applying the boundary condition (4.2) for points of x, y inside $x^2/a^2+y^2/b^2 = 1$ and $z \to 0^+$, (4.9) may be written as

$$\frac{ab\,q(x,y)}{4(1-\nu)} = \lim_{\xi\to 0}\left[(\xi\eta\zeta)^{\frac{1}{2}}\int_{\xi}^{\infty}\lambda'(\omega)\frac{ds}{s\sqrt{Q(s)}}\right] + \frac{ab\,\lambda(0)}{(\eta\zeta)^{\frac{1}{2}}}. \tag{5.1}$$

The reduction of (5.1) to Abel's equation may be accomplished by changing the variable of integration from s to $\alpha = 1 - \xi/s$ and by keeping in mind that ω is a function of s with the limiting form

$$\omega(s) \to \frac{\alpha\eta\zeta}{a^2b^2}, \qquad \text{as} \qquad \xi \to 0$$

where

$$\eta\zeta \to a^2b^2Z, \quad \text{and} \quad Z = 1 - \frac{x^2}{a^2} - \frac{y^2}{b^2}. \tag{5.2}$$

Under these considerations, (5.1) reduces to

$$\frac{ab\,q(Z)}{4(1-\nu)} - Z^{\frac{1}{2}}\int_0^1 \lambda'(\alpha Z)\frac{d\alpha}{\sqrt{1-\alpha}} + \frac{\lambda(0)}{Z^{\frac{1}{2}}} \cdot \tag{5.3}$$

An additional change of variable to $\beta = \alpha Z$ gives the Abel integral equation [6]

$$\frac{ab\,q(Z)}{4(1-\nu)} = \int_0^Z \frac{\lambda'(\beta)\,d\beta}{\sqrt{Z-\beta}} + \frac{\lambda(0)}{Z^{\frac{1}{2}}} \cdot \tag{5.4}$$

In order to solve for $\lambda(\omega)$, both sides of (5.4) are integrated from o to ω by $dZ/\sqrt{\omega - Z}$. Hence, (5.4) becomes

$$\int_0^\omega \frac{\lambda(0)\,dZ}{Z^{1/2}\sqrt{\omega-Z}} + \int_0^\omega \frac{dZ}{\sqrt{\omega-Z}}\int_0^Z \frac{\lambda'(\beta)\,d\beta}{\sqrt{Z-\beta}} = \frac{ab}{4(1-\nu)}\int_0^\omega \frac{q(Z)\,dZ}{\sqrt{\omega-Z}} \cdot \tag{5.5}$$

The integrals on the left hand side of (5.5) may be evaluated without difficulty the first of which is

$$\int_0^\omega \frac{\lambda(0)\,dZ}{Z^{1/2}\sqrt{\omega-Z}} = 2\int_0^{\frac{\pi}{2}} \lambda(0)\,d\theta = \pi\lambda(0). \tag{5.6}$$

The order of integration of the second integral

$$\int_0^\omega \frac{dZ}{\sqrt{\omega-Z}}\int_0^Z \frac{\lambda'(\beta)\,d\beta}{\sqrt{Z-\beta}} \tag{5.7}$$

may be interchanged since the integrands possess weak singularities. Application of the Dirichlet formula [7] gives

$$\int_0^\omega \lambda'(\beta)\,d\beta\int_\beta^\omega \frac{dZ}{\sqrt{(\omega-Z)(Z-\beta)}} = \pi\int_0^\omega \lambda'(\beta)\,d\beta = \pi[\lambda(\omega)-\lambda(0)]. \tag{5.8}$$

Substituting both (5.6) and (5.8) into (5.5) yields the solution of (5.4) as

$$\lambda(\omega) = \frac{ab}{4\pi(1-\nu)}\int_0^\omega \frac{q(Z)\,dZ}{\sqrt{\omega-Z}} \cdot \tag{5.9}$$

Thus, (5.9) solves the problem of prescribing normal displacements q(Z) on an elliptically-shaped plane of discontinuity.

6. Theorem. On the basis of the results obtained in the previous section,

the following theorem may be established:

"Let the normal displacements, $q(x,y)$, on the plane surfaces of the ellipse $x^2/a^2+y^2/b^2 = 1$ be given by $(1 - \frac{x^2}{a^2} - \frac{y^2}{b^2})^{\frac{1}{2}} Q_n(x^2,y^2)$, where $Q_n(x^2,y^2)$ is a polynomial of degree n in x^2, y^2. Then, the normal pressure acting over the ellipse is also a polynomisl, $P_n(x^2,y^2)$, of the same degree in x^2,y^2."

Now, suppose that

$$q(x,y) = Z^{\frac{1}{2}} \sum_{j=0}^{n} C_j Z^j . \tag{6.1}$$

It suffices to prove the theorem by taking $Q_n(x^2,y^2)$ in the form of (6.1). The coefficients C_j $(j=0,1,\cdots,n)$ are constants and Z is given by (5.2). Putting (6.1) into (5.9) and carrying out the integration yields

$$\lambda(\omega) = \frac{ab}{4(1-\nu)\sqrt{\pi}} \sum_{j=0}^{n} \frac{\Gamma(j+\frac{3}{2})}{(j+1)!} C_j [\omega(s)]^{j+1} , \tag{6.2}$$

in which $\Gamma(n)$ is the customary Gamma function. Before the normsl pressure σ_{zz} csn be calculated, the harmonic function f(x,y,z) must be obtained from (4.4):

$$f(x,y,z) = \frac{ab}{4(1-\nu)\sqrt{\pi}} \sum_{j=0}^{n} \frac{\Gamma(j+\frac{3}{2})}{(j+1)!} C_j \int_{\xi}^{\infty} [\omega(s)]^{j+1} \frac{ds}{\sqrt{Q(s)}} . \tag{6.3}$$

In the plane z = o, (2.6) simplifies to

$$(\sigma_{zz})_{z=0} = 2\mu \left(\frac{\partial^2 f}{\partial x^2} + \frac{\partial^2 f}{\partial y^2} \right)_{z=0} . \tag{6.4}$$

Adopting the notstion

$$\gamma = \begin{cases} 0 , & \left(\frac{x^2}{a^2} + \frac{y^2}{b^2} < 1, z=0 \right) \\ \xi , & \left(\frac{x^2}{a^2} + \frac{y^2}{b^2} > 1, z=0 \right) \end{cases} \tag{6.5}$$

and using (6.3), it is found thst

$$(\sigma_{zz})_{z=0} = -\frac{ab\mu}{(1-\nu)\sqrt{\pi}} \sum_{j=0}^{n} \frac{\Gamma(j+\frac{3}{2})}{j!} C_j \left\{ \int_{\gamma}^{\infty} \left(\frac{1}{a^2+s} + \frac{1}{b^2+s} \right) [\omega_0(s)]^j \frac{ds}{\sqrt{Q(s)}} \right. \tag{6.6}$$

$$-2j\int_{\gamma}^{\infty}\left[\left(\frac{x}{a^2+s}\right)^2+\left(\frac{y}{b^2+s}\right)^2\right]\left[\omega_0(s)\right]^{j-1}\frac{ds}{\sqrt{Q(s)}}\Bigg\}\ ,$$

where

$$\omega_0(s)=\left[\omega(s)\right]_{z=0}=1-\frac{x^2}{a^2+s}-\frac{y^2}{b^2+s}\ .$$

The integrands containing $\left[\omega_0(a)\right]^n$, $(n=1,2,\cdots)$, may be expanded in terms of x^2, y^2 to give

$$(\sigma_{zz})_{z=0}=A_0+A_1x^2+A_2y^2+\cdots=P_n(x^2,y^2)\ , \qquad (6.7)$$

in which A_j $(j=0,1,2,\cdots,n)$ are

$$A_0=B_0\int_{\gamma}^{\infty}\left(\frac{1}{a^2+s}+\frac{1}{b^2+s}\right)\frac{ds}{\sqrt{Q(s)}}\ ,$$

$$A_1=B_1\int_{\gamma}^{\infty}\frac{ds}{(a^2+s)(b^2+s)\sqrt{Q(s)}}+B_2\int_{\gamma}^{\infty}\frac{ds}{(a^2+s)^2\sqrt{Q(s)}}\ ,$$

$$A_2=B_1\int_{\gamma}^{\infty}\frac{ds}{(a^2+s)(b^2+s)\sqrt{Q(s)}}+B_2\int_{\gamma}^{\infty}\frac{ds}{(b^2+s)^2\sqrt{Q(s)}}\ ,$$

and so on. The constants $B_0, \cdots, B_2$ are related to C_j $(j=0,1,2)$ as follows:

$$B_0=-\frac{ab\mu}{(1-\nu)\sqrt{\pi}}\sum_{j=0}^{n}\frac{\Gamma(j+\frac{3}{2})}{j!}C_j\ ,\quad B_1=\frac{ab\mu}{(1-\nu)\sqrt{\pi}}\sum_{j=1}^{n}\frac{\Gamma(j+\frac{3}{2})}{(j-1)!}C_j\ ,\quad B_2=3B_1\ .$$

From (6.7), $(\sigma_{zz})_{z=0}$ is seen to be a polynomial of degree n in x^2, y^2 whose coefficients depend on

$$\int_{\gamma}^{\infty}\frac{ds}{(a^2+s)^{n+1}\sqrt{Q(s)}}\ ,\quad \int_{\gamma}^{\infty}\frac{ds}{(a^2+s)^{n+1}(b^2+s)^{n+1}\sqrt{Q(s)}}\ ,\quad \int_{\gamma}^{\infty}\frac{ds}{(b^2+s)^{n+1}\sqrt{Q(s)}}\ ,\quad n=0,1,\cdots$$

These integrals can be reduced to the complete elliptic integrals of the first and second kind with modulus $k^2=1-(b/a)^2$ for $\xi=0$.

The aforementioned theorem also applies to the skew-symmetric problem of specifying displacements u, v on the elliptical plane of discontinuity. This is mainly because the boundary conditions on u, v are the same as those described by (4.2) and (4.3) since Kassir and Sih [4] have already shown that for the skew-symmetric case the displacements are

$$u = -2(1-\nu)\frac{\partial q}{\partial x} + z\frac{\partial G}{\partial x},$$

$$v = -2(1-\nu)\frac{\partial h}{\partial y} + z\frac{\partial G}{\partial y},$$

$$w = -(1-2\nu)G + z\frac{\partial G}{\partial z},$$

where

$$G = \frac{\partial q}{\partial x} + \frac{\partial h}{\partial y},$$

and

$$\nabla^2 q(x,y,z) = 0, \qquad \nabla^2 h(x,y,z) = 0.$$

For this problem, the shear stresses τ_{xz}, τ_{yz} will be polynomials of degree n in x^2, y^2 if the displacements u, v are represented by polynomials of the form (6.1).

In the two-dimensional case, Sneddon [1] has observed that the prescribed shape of a slit in an isotropic medium and the resulting surface pressure may be represented by polynomials of the same degree in one variable. Galin [8] has considered the three-dimensional problem of an elliptical punch pressing against a semi-infinite elastic solid whose surface outside the area of contact is free from tractions. The frictional forces acting between the punch and the semi-infinite body are neglected. He showed that if the base profile of the punch is given by a polynomial of degree n in x, y, then the pressure acting over the punch is another polynomial. Galin's proof is based upon the properties of Lamé triple product, which is different from that given in the present paper.

7. The Symmetric Problem. A sufficiently general description of the shape of the elliptical plane of discontinuity is

$$q(Z) = q_0 Z^n, \tag{7.1}$$

where q_0 denotes the amplitude of the normal displacement. The restriction on the exponent n becomes apparent when the functions

$$\lambda(\omega) - \frac{ab q_0}{4\pi(1-\nu)} \int_0^{\omega} \frac{Z^n dZ}{\sqrt{\omega - Z}} = \frac{ab q_0}{4(1-\nu)\sqrt{\pi}} \frac{\Gamma(n+1)}{\Gamma(n+\frac{3}{2})} [\omega(s)]^{n+\frac{1}{2}}, \quad n > -1, \qquad (7.2)$$

and

$$f(x,y,z) = \frac{ab q_0 \Gamma(n+1)}{4(1-\nu)\sqrt{\pi}\,\Gamma(n+\frac{3}{2})} \int_{\xi}^{\infty} [\omega(s)]^{n+\frac{1}{2}} \frac{ds}{\sqrt{Q(s)}}, \quad n > -1, \qquad (7.3)$$

are derived from (5.9) and (4.4), respectively. The normal pressure distribution required to support the shape (7.1) can be obtained from (6.4) and (7.3). For the range of n between 1/2 and 3/2, σ_{zz} in the plane z = o is

$$(\sigma_{zz})_{z=0} = -\frac{ab\mu q_0 (n+\frac{1}{2})\Gamma(n+1)}{(1-\nu)\sqrt{\pi}\,\Gamma(n+\frac{3}{2})} \left[I_1 + I_2 + x \frac{\partial I_1}{\partial x} + y \frac{\partial I_2}{\partial y} \right], \quad \frac{1}{2} \le n < \frac{3}{2}, \qquad (7.4)$$

where I_1, I_2 represent the integrals

$$I_1 = \int_{\gamma}^{\infty} \frac{[\omega_0(s)]^{n-\frac{1}{2}}}{(a^2+s)} \frac{ds}{\sqrt{Q(s)}}, \qquad I_2 = \int_{\gamma}^{\infty} \frac{[\omega_0(s)]^{n-\frac{1}{2}}}{(b^2+s)} \frac{ds}{\sqrt{Q(s)}}$$

and γ is defined by (6.5). If $n \ge 3/2$, the expression for $(\sigma_{zz})_{z=0}$ is less complicated:

$$(\sigma_{zz})_{z=0} = -\frac{ab\mu q_0 (n+\frac{1}{2})\Gamma(n+1)}{(1-\nu)\sqrt{\pi}\,\Gamma(n+\frac{3}{2})} \left\{ \int_{\gamma}^{\infty} \left(\frac{1}{a^2+s} + \frac{1}{b^2+s} \right) [\omega_0(s)]^{n-\frac{1}{2}} \frac{ds}{\sqrt{Q(s)}} \right.$$
$$\left. - (2n-1) \int_{\gamma}^{\infty} \left[\left(\frac{x}{a^2+s} \right)^2 + \left(\frac{y}{b^2+s} \right)^2 \right] [\omega_0(s)]^{n-\frac{3}{2}} \frac{ds}{\sqrt{Q(s)}} \right\}, \quad n \ge \frac{3}{2}. \qquad (7.5)$$

In general, the integrals appearing in (7.4) and (7.5) can be evaluated for n = m + ½, where m = o,1,2, ···, . In the degenerate case of a circular region of discontinuity, solutions may be found for any value of n.

8. Elliptical Region for n = 1/2 and n = 3/2. A special case of (7.4) is n = 1/2, which corresponds to the problem of a plane elliptical cut opened by a normal pressure, $(\sigma_{zz})_{z=0}$ = constant. The opening of the cut is ellipsoidal given by

$$f(Z) = q_0 Z^{\frac{1}{2}}.$$

This problem was formulated by Green ans Sneddon [3]. In a later paper, Kassir and Sih [4] pointed out that the stresses at the border of the cut

are singular of the order of $1/\sqrt{\rho}$. The distance ρ is measured in a plane perpendicular to the boundary of the ellipse $x^2/a^2+y^2/b^2 = 1$.

Therefore, it is natural to inquire whether cuts of a shape other than ellipsoidal are possible and, if they exist, to determine the pressure necessary to preserve their shape. Consider the case

$$q(Z) = q_0 Z^{3/2}. \tag{8.1}$$

For n = 3/2, (7.5) specializes to

$$(\sigma_{zz})_{z=0} = -\frac{3ab\mu q_0}{4(1-\nu)}\left[\int_\gamma^\infty \left(\frac{1}{a^2+s}+\frac{1}{b^2+s}\right)\frac{ds}{\sqrt{Q(s)}} - 3x^2\int_\gamma^\infty \frac{ds}{(a^2+s)^2\sqrt{Q(s)}}\right.$$
$$\left. -3y^2\int_\gamma^\infty \frac{ds}{(b^2+s)^2\sqrt{Q(s)}} - (x^2+y^2)\int_\gamma^\infty \frac{ds}{(a^2+s)(b^2+s)\sqrt{Q(s)}}\right]. \tag{8.2}$$

The integrals in (8.2) may be evaluated in a manner similar to those shown in (3.32) and (3.33).

The normal pressure inside of the elliptical region, $\gamma = 0$, is

$$(\sigma_{zz})_{z=0} = -\frac{3b\mu q_0}{2(1-\nu)a^2k^2}\left\{\left(\frac{k}{k'}\right)^2 E(k) - \left(\frac{x}{b}\right)^2\left[k'^2K(k)+(k^2-k'^2)E(k)\right]\right.$$
$$\left. -\left(\frac{y}{b}\right)^2\left[\frac{1+k^2}{k'^2}E(k)-K(k)\right]\right\}. \tag{8.3}$$

When a = b and $E(k) = K(k) = \pi/2$, (8.3) gives the internal pressure for a penny-shaped cut of radius s, i.e.,

$$(\sigma_{zz})_{z=0} = -\frac{3\mu\pi}{4(1-\nu)}\left(\frac{q_0}{a}\right)\left[1-\frac{3}{2}\left(\frac{r}{a}\right)^2\right], \quad r<a \tag{8.4}$$

The sign of $(\sigma_{zz})_{z=0}$ changes from negative to positive at the ratio of $(r/a) \simeq 0.8$. This means that both compressive and tensile stresses must be applied to the surfaces of the cut in order to produce the shape (8.1).

Outside of the region of the ellipse, $(\sigma_{zz})_{z=0}$ may be found by setting $\gamma = \xi$ in (8.2):

$$(\sigma_{zz})_{\eta=0} = -\frac{3\mu}{2(1-\nu)}\left(\frac{q_0}{b}\right)\left\{E(u) - \frac{\mathrm{sn}\,u\,\mathrm{cn}\,u}{\mathrm{dn}\,u} - \right. \tag{8.5}$$

$$-\left(\frac{x}{ak}\right)^2\left[k'^2u+(1-2k'^2)E(u)+\frac{\operatorname{sn}u\,\operatorname{cn}u}{\operatorname{dn}u}(k'^2\operatorname{dn}^2u-1)\right]$$

$$-\left(\frac{y}{ak}\right)^2\left[\left(\frac{k^2}{k'^2}-1\right)E(u)-u-\frac{\operatorname{sn}u\,\operatorname{cn}u}{\operatorname{dn}u}\left(\frac{1}{\operatorname{dn}u}+2\frac{k^2}{k'^2}-1\right)\right]\Bigg\}\,.$$

In contrast to the singular solution for n = 1/2, the stresses remain finite on the boundary of the elliptical cut. In fact, in the limit as $\xi \to 0$, (8.5) is of the order of $\rho^{1/2}$. The same behavior is observed for the particular case of a = b since (8.5) reduces to

$$(\sigma_{zz})_{z=0}=-\frac{3\mu}{2(1-\nu)}\left(\frac{q_0}{a}\right)\left\{\left[1-\frac{3}{2}\left(\frac{r}{a}\right)^2\right]\sin^{-1}\left(\frac{a}{r}\right)+\frac{3}{2}\left[\left(\frac{r}{a}\right)^2-1\right]^{\frac{1}{2}}\right\},\quad r>a, \tag{8.6}$$

where $(\sigma_{zz})_{z=0}$ goes to infinity as $O(1/r^3)$. When r approaches a, the circular boundary, the normal pressure

$$(\sigma_{zz})_{z=0}=\frac{3\mu\pi}{8(1-\nu)}\left(\frac{q_0}{a}\right),\quad r=a \tag{8.7}$$

is found to be non-singular.

It should be mentioned that (8.4) and (8.6) may be obtained directly from the method of Hankel transform for solving axially symmetric problems [9].

9. Circular Region for Arbitrary n. The theory of potential functions may also be applied expediently to a class of problems involving penny-shaped planes of discontinuities. For a = b, (7.4) can be solved in general without imposing restrictions on the exponent n as $I_1 = I_2 = I$ and

$$(\sigma_{zz})_{z=0}=-\frac{a^2\mu\,q_0\,(n+\frac{1}{2})\,\Gamma(n+1)}{(1-\nu)\sqrt{\pi}\,\Gamma(n+\frac{3}{2})}\left[2I+\left(x\frac{\partial}{\partial x}+y\frac{\partial}{\partial y}\right)I\right]. \tag{9.1}$$

The integral I is

$$I=\int_\gamma^\infty\frac{\left[(s-\xi)(s-\eta)\right]^{n-\frac{1}{2}}}{s^n(a^2+s)^{n+\frac{3}{2}}}\,ds\,, \tag{9.2}$$

and the symbol γ stands for

$$\gamma=\begin{cases}0\,, & r<a\\ r^2-a^2\,, & r>a\,.\end{cases} \tag{9.3}$$

Making the substitutions

$$\sigma^2 = \frac{s-\xi}{s-\eta} \quad , \quad \epsilon^2 = \frac{a^2+\eta}{a^2+\xi} \, ,$$

in (9.2), the integral I becomes

$$I = \frac{2(\xi-\eta)^{2n}}{(a^2+\xi)^{n+\frac{3}{2}}} \int_0^1 \frac{\sigma^{2n}\sqrt{1-\sigma^2}\, d\sigma}{(\xi-\sigma^2\eta)^n (1-\epsilon^2\sigma^2)^{n+\frac{3}{2}}} \, . \qquad (9.4)$$

The determination of $(\sigma_{zz})_{z=0}$ for $r<a$ and $r>a$ will be carried out seperately.

Inside of the region $x^2+y^2 = a^2$ and for $z = 0$, the ellipsoidal coordinates ξ, η take the values

$$\xi = 0, \quad \eta = r^2 - a^2 ,$$

and $\epsilon^2 = k^2 = (r/a)^2$. Hence, (9.4) reduces to the standard Legendre elliptic integral

$$(I)_{\xi=0} = \frac{2k'^{2n}}{a^3} \int_0^1 \frac{\sqrt{1-\sigma^2}\, d\sigma}{(1-k^2\sigma^2)^{n+\frac{3}{2}}} \, , \qquad (9.5)$$

where

$$k'^2 = 1 - \left(\frac{r}{a}\right)^2 .$$

A further substitution of $\sigma = \mathrm{sn}\, u$ leads to

$$(I)_{\xi=0} = \frac{2}{a^3}\left(\frac{k'^{2n}}{k^2}\right)\left(J_{2n} - k'^2 J_{2n+2}\right) . \qquad (9.6)$$

In (9.6), J_m represents the integral

$$J_m = \int_0^K (\mathrm{nd}\, u)^m du \, , \qquad (9.7)$$

whose values for $m = 0,1,2, \cdots$, are given by [10]

$$J_0 = K(k) \, , \; J_1 = \frac{\pi}{2k'} \, , \; J_2 = \frac{E(k)}{k'^2} \, , \; J_3 = \frac{(2-k^2)\pi}{4k'^3} \, , \cdots \, , \qquad (9.8)$$

and the recurrence formulas

$$J_{2m+2} = \frac{1}{(2m+1)k'^2}\left[2m(2-k^2)J_{2m} + (1-2m)J_{2m-2}\right] , \qquad (9.9)$$

$$J_{2m+3} = \frac{1}{2(m+1)k'^2}\left[(2m+1)(2-k^2)J_{2m+1} - 2m\, J_{2m-1}\right] . \qquad (9.10)$$

In order to complete the calculation of $(\sigma_{zz})_{z=0}$ for $\xi = 0$, it is necessary to find from (9.2) the quantity

$$\left[\left(x\frac{\partial}{\partial x}+y\frac{\partial}{\partial y}\right)I\right]_{\xi=0} = 2r^2\left(\frac{\partial I}{\partial \eta}\right)_{\xi=0}. \tag{9.11}$$

Some lengthy algebra gives

$$\left(\frac{\partial I}{\partial \eta}\right)_{\xi=0} = -\frac{k'^{2n}}{a^5}\left[\frac{2n}{k'^2}\int_0^1 \frac{\sqrt{1-\sigma^2}\,d\sigma}{(1-k^2\sigma^2)^{n+\frac{3}{2}}} - (2n+3)\int_0^1 \frac{\sigma^2\sqrt{1-\sigma^2}\,d\sigma}{(1-k^2\sigma^2)^{n+\frac{5}{2}}}\right]$$

$$= -\frac{k'^{2n}}{a^5k^2}\left\{\frac{2n}{k'^2}\left(J_{2n}-k'^2J_{2n+2}\right) + \left(\frac{2n+3}{k^2}\right)\left[J_{2n}-(1+k'^2)J_{2n+2}+k'^2J_{2n+4}\right]\right\}, \tag{9.12}$$

where J_m is given by (9.7). Using (9.1), the internal pressure, $(\sigma_{zz})_{z=0}$, in the region $r<a$ takes the form

$$(\sigma_{zz})_{\xi=0} = -\frac{2\mu(n+\frac{1}{2})\Gamma(n+1)}{(1-\nu)\sqrt{\pi}\,\Gamma(n+\frac{3}{2})}\left(\frac{q_0}{a}\right)\left(\frac{k'^{2n}}{k^2}\right)\left[-\left(1+\frac{2n}{k'^2}\right)J_{2n} + (3+4n+k'^2)J_{2n+2} - (2n+3)k'^2J_{2n+4}\right], \tag{9.13}$$

which is valid for arbitrary value of n. Three special cases of (9.13) will be considered by application of (9.8)-(9.10).

Case 9.1(a). The necessary normal pressure to maintain the shape

$$f(r) = q_0\left[1-\left(\frac{r}{a}\right)^2\right]^{\frac{1}{2}}$$

may be computed from (9.13) by setting n = 1/2 as

$$(\sigma_{zz})_{\xi=0} = -\frac{\mu}{1-\nu}\left(\frac{q_0}{a}\right)\left(\frac{k'}{k^2}\right)\left[-\left(1+\frac{1}{k'^2}\right)J_1 + (5+k'^2)J_3 - 4k'^2J_5\right] \tag{9.14}$$

$$= -\frac{\mu\pi}{2(1-\nu)}\left(\frac{q_0}{a}\right), \quad r<a.$$

This is in agreement with Sneddon's answer [9].

Case 9.2(a). If n = 1, (9.13) simplifies to

$$(\sigma_{zz})_{\xi=0} = -\frac{4\mu}{(1-\nu)\pi}\left(\frac{q_0}{a}\right)\left(\frac{k'}{k}\right)^2\left[-\left(1+\frac{2}{k'^2}\right)J_2 + (7+k'^2)J_4 - 5k'^2J_6\right]$$

$$= \frac{4\mu}{(1-\nu)\pi}\left(\frac{q_0}{a}\right)\left[K\left(\frac{r}{a}\right) - 2E\left(\frac{r}{a}\right)\right], \quad r<a. \tag{9.15}$$

At first sight, (9.15) appears to be different from the solution published

by Sneddon [9] for the same problem, i.e.,

$$(\sigma_{zz})_{z=0} = -\frac{4\mu}{(1-\nu)\pi}\left(\frac{q_0}{a}\right)\left[\frac{1+(r/a)^2}{1+(r/a)}K(k^*) - K\left(\frac{r}{a}\right) - \left(1+\frac{r}{a}\right)E(k^*)\right], \qquad (9.16)$$

in which

$$k^{*2} = \frac{4ar}{(a+r)^2}.$$

However, by means of the Landen transformation, the complete elliptic integrals in (9.16) can be written as

$$\left(1+\frac{r}{a}\right)E(k^*) = 2E\left(\frac{r}{a}\right) - \left[1-\left(\frac{r}{a}\right)^2\right]K\left(\frac{r}{a}\right), \qquad (9.17)$$

$$K(k^*) = \left(1+\frac{r}{a}\right)K\left(\frac{r}{a}\right). \qquad (9.18)$$

The identities (9.17), (9.18) show that (9.16) and (9.15) are indeed equivalent.

Case 9.3(a). In the case of n = 3/2, (8.4) is recovered from (9.13) since

$$(\sigma_{zz})_{\xi=0} = -\frac{3\mu}{2(1-\nu)}\left(\frac{q_0}{a}\right)\left(\frac{k'^3}{k^2}\right)\left[-\left(1+\frac{3}{k'^2}\right)J_3 + (9+k'^2)J_5 - 6k'^2J_7\right]$$

$$= -\frac{3\mu\pi}{4(1-\nu)}\left(\frac{q_0}{a}\right)\left[1-\frac{3}{2}\left(\frac{r}{a}\right)^2\right]. \qquad (9.18)$$

In the same fashion, $(\sigma_{zz})_{z=0}$ outside of the circular plane of discontinuity may be obtained by letting

$$\left[\left(x\frac{\partial}{\partial x}+y\frac{\partial}{\partial y}\right)I\right]_{\eta=0} = 2r^2\left(\frac{\partial I}{\partial \xi}\right)_{\eta=0}, \qquad (9.19)$$

and

$$(I)_{\eta=0} = \frac{2k'^{2n}}{r^3}\int_0^1 \frac{\sigma^{2n}\sqrt{1-\sigma^2}\,d\sigma}{(1-k^2\sigma^2)^{n+\frac{3}{2}}}, \qquad (9.20)$$

which is found from (9.4) for $\eta = 0$, $\epsilon = k = (a/r)$, and $\xi = r^2 - a^2$. The substitution $\sigma = s\nu$ allows (9.20) to be

$$(I)_{\eta=0} = \frac{2k'^{2n}}{r^3k^2}\left(M_{2n} - k'^2N_{2n}\right), \quad k = \frac{a}{r}, \qquad (9.21)$$

where

$$M_m = \int_0^K \left(\frac{sn u}{dn u}\right)^m du , \tag{9.22}$$

$$N_{2n} = \int_0^K \frac{(sn u)^{2n}}{(dn u)^{2n+2}} du , \tag{9.23}$$

The integrals (9.22) can be expressed in terms of the complete elliptic integrals and elementary functions in the following manner [10] :

$$M_1 = \frac{\sin^{-1}(k) - \sin^{-1}(2kk')}{k k'} , \quad M_2 = \frac{E(k) - k'^2 K(k)}{k^2 k'^2} , \quad M_3 = \frac{M_1}{2kk'} , \quad \cdots . \tag{9.24}$$

The recurrence relationships are

$$M_{2m+2} = \frac{1}{(2m+1)k^2 k'^2}\left[2m(2k^2-1)M_{2m} + (2m-1)M_{2m-2}\right] , \tag{9.25}$$

$$M_{2m+3} = \frac{1}{2(m+1)k^2 k'^2}\left[(2m+1)(2k^2-1)M_{2m+1} + 2m\, M_{2m}\right] . \tag{9.26}$$

In addition, the integral (9.23) admits the relations

$$N_0 = \frac{E(k)}{k'^2} , \quad N_1 = \frac{1}{3k^2 k'^4}\left[(1+k^2)E(k) - k'^2 K(k)\right] , \quad \cdots ,$$
$$N_{m+2} = \frac{1}{(5+2m)k^2 k'^2}\left[(2m+1)N_m + 2(3k^2 + 2mk^2 - m - 1)N_{m+1}\right] , \tag{9.27}$$

in which

$$N_m = \int_0^K \frac{(sn u)^{2m}}{(dn u)^{2m+2}} du .$$

If the exponent n = m/2, m being an integer, then (9.20) is reducible to elementary functions. Finally, the normal pressure for r>a is deduced:

$$(\sigma_{zz})_{\eta=0} = -\frac{2\mu(n+\frac{1}{2})\Gamma(n+1)}{(1-\nu)\pi\,\Gamma(n+\frac{3}{2})}\left(\frac{q_0}{r}\right) k'^{2n}\left[2n\left(\frac{1}{k'^2} - \frac{1}{2n}\right)\right. \qquad _{n} - k'^2 N_{2n})$$
$$\left. - (2n+3)k^2\left(M_{2n+2} - k'^2 N_{2n+2}\right)\right] . \tag{9.28}$$

The valuee of $(\sigma_{zz})_{\eta=0}$ that correspond to n = 1/2, 1, 3/2 are as follows:

Case 9.1(b). Ineteed of ueing (9.28), it ie simpler in the caee of n=½ to compute $(\sigma_{zz})_{\eta=0}$ directly from (9.1),

$$(\sigma_{zz})_{\eta=0} = -\frac{\mu}{1-\nu}\left(\frac{q_0}{r}\right)k^2k'\left[\left(\frac{1}{k'^2}-2\right)\int_0^1 \frac{\sigma\sqrt{1-\sigma^2}\,d\sigma}{(1-k^2\sigma^2)^2} - 4k^2\int_0^1 \frac{\sigma^3\sqrt{1-\sigma^2}\,d\sigma}{(1-k^2\sigma^2)^3}\right]. \tag{9.29}$$

These integrale are elementery giving

$$(\sigma_{zz})_{\eta=0} = -\frac{\mu}{1-\nu}\left(\frac{q_0}{r}\right)\left[\sin^{-1}\left(\frac{a}{r}\right) - \frac{1}{\sqrt{\left(\frac{r}{a}\right)^2-1}}\right], \quad r>a \tag{9.30}$$

which checks with thet obatined by Sneddon [9].

Case 9.2(b). Letting n = 1 in (9.28) end carrying out the elgebra render

$$(\sigma_{zz})_{\eta=0} = \frac{4\mu}{(1-\nu)\pi}\left(\frac{q_0}{a}\right)\left[\left(2\frac{r}{a}-\frac{a}{r}\right)K\left(\frac{a}{r}\right) - 2\frac{r}{a}E\left(\frac{a}{r}\right)\right], \quad 1<\frac{r}{a}<\infty, \tag{9.31}$$

which ie O(1/r) for lerge r. At the boundery pointe of r = e, $(\sigma_{zz})_{\eta=0}$ ie unbounded.

Case 9.3(b). The limiting form of (9.28) for n = 3/2 corresponde pracisely to (8.6) which hes alreedy been diecussed.

10. Conclusion. The problem of finding streeeee and displecements in en elestic eolid with geometric diecontinuities hee been reduced to the claesical boundary problem of potentiel theory. Hermonic functione are developed for the case of en elliptically-eheped plane of discontinuity whose faces are subjected to preseures end/or dieplecemente. While the present peper ie primarily concerned with the celculetion of the normal displecement w and the corresponding pressure σ_{zz}, the remeining dieplacements and streeses mey be obteined from (2.1), (2.2), (2.4), end (2.5) without difficulty. Furthermore, with the knowledge of f(x,y,z), the strees components [2]

$$\sigma_{xx} = 2\mu \left(\frac{\partial^2 f}{\partial x^2} + 2\nu \frac{\partial^2 f}{\partial y^2} + z \frac{\partial^3 f}{\partial z \partial x^2} \right), \qquad (10.1)$$

$$\sigma_{yy} = 2\mu \left(\frac{\partial^2 f}{\partial y^2} + 2\nu \frac{\partial^2 f}{\partial x^2} + z \frac{\partial^3 f}{\partial z \partial y^2} \right), \qquad (10.2)$$

$$\tau_{xy} = 2\mu \left[(1-2\nu) \frac{\partial^2 f}{\partial x \partial y} + z \frac{\partial^3 f}{\partial x \partial y \partial z} \right], \qquad (10.3)$$

are also known. The method of solution outlined in the paper may be used to solve other boundary problems of fundamental interest. For example, the skew-symmetric problem of specifying displacements u, v on the surfaces of the geometric discontinuity may be formulated and solved in a similar manner.

REFERENCES

1 Sneddon, I. N., "Crack Problems in the Mathematical Theory of Elasticity", North Carolina State College Publications, Raleigh, (1961).

2 Green, A. E., and Zerna, W., "Theoretical Elasticity", Oxford Press, London, (1960).

3 Green, A. E., and Sneddon, I. N., "The Distribution of Stress in the Neighborhood of a Flat Elliptical Crack in an Elastic Solid", Proceedings of Cambridge Philosophical Society, Vol. 46, (1950), 159-164.

4 Kassir, M. K., and Sih, G. C., "Three-Dimensional Stress Distribution Around an Elliptical Crack under Arbitrary Loadings", Journal of Applied Mechanics (In Press).

5 Kellogg, O. D., "Foundation of Potential Theory", Dover Publications, Inc., New York, (1953).

6 Rostovtsev, N. A., "On Certain Solutions of an Integral Equation of the Theory of a Linearly Deformable Foundation", Applied Mathematics and Mechanics (PMM), Vol. 28, (1964), 111-127.

7 Whittaker, E. T., and Watson, G. N., "Modern Analysis", Cambridge Press, London, (1962).

8 Galin, L. A., "Contact Problems in the Theory of Elasticity", North Carolina State College Publications, Raleigh, (1961).

9 Sneddon, I. N., "Fourier Transforms", McGraw-Hill Book Company, Inc., New York, (1951).

10 Byrd, P. F., and Friedman, M. D., "Handbook of Elliptic Integrals for Engineers and Physicists", Springer-Verlag, Berlin, (1954).

PART I - GOVERNMENT

Administrative & Liaison Activities

Chief of Naval Research
Attn: Code 102 (Dr. F. J. Weyl)
423
439 (2)
468
Department of the Navy
Washington, D. C. 20360

Commanding Officer
ONR Branch Office
495 Summer Street
Boston, Massachusetts 02210

Commanding Officer
ONR Branch Office
219 S. Dearborn Street
Chicago, Illinois 60604

Commanding Officer
ONR Branch Office
Box 39, Navy 100
c/o Fleet Post Office
New York, New York 09510 (5)

Commanding Officer
ONR Branch Office
207 West 24th Street
New York New York 10011

Commanding Officer
ONR Branch Office
1030 E. Green Street
Pasadena, California 91101

Commanding Officer
ONR Branch Office
U.S. Post Office & Courts Bldg.
1076 Mission Street
San Francisco, California 94103

U. S. Naval Research Laboratory
Attn: Technical Information Div.
Washington, D. C. 20390 (6)

Defense Documentation Center
Cameron Station
Alexandria, Virginia 22314 (20)

Army

Commanding Officer
U. S. Army Research Off.-Durham
Attn: Mr. J. J. Murray
CRD-AA-IP
Box CM, Duke Station
Durham, North Carolina 27706

Commanding Officer
AMXMR-ATL
U. S. Army Materials Res. Agcy.
Watertown, Massachusetts 02172

Redstone Scientific Info. Center
Chief, Document Section
U. S. Army Missile Command
Redstone Arsenal, Alabama 35809

AMSMI-RKP
Attn: Mr. T. H. Duerr
Redstone Arsenal, Alabama 35809

Ballistic Research Laboratories
Attn: Dr. A. S. Elder
Aberdeen Proving Ground
Aberdeen, Maryland 21005

Ballistic Research Laboratories
Attn: Mr. H. P. Gay
AMXBR-ID
Aberdeen Proving Ground
Aberdeen, Maryland 21005

Technical Library
Aberdeen Proving Ground
Aberdeen, Maryland 21005

Navy

Commanding Officer and Director
Attn: Code 042 (Cent. Lib. Br.)
050
700 (Struc. Mech. Lab.)
720
725
740 (Mr. W. J. Sette)
901 (Dr. M. Strassberg)
941 (Dr. R. Liebowitz)
945 (Mr. A. O. Sykes)
960 (Mr. E. F. Noonan)
962 (Dr. E. Buchmann)
David Taylor Model Basin
Washington, D. C. 20007

Navy (cont'd.)

Director
Aeronautical Structures Lab.
Naval Air Engineering Center
Naval Base
Philadelphia, Pennsylvania 19112

Director
Attn: Code 5360
5500
6200
6210
6250
6260
Technical Library
Naval Research Laboratory
Washington, D. C. 20390

Chief, Bureau of Naval Weapons
Attn: Code DLI-3
R-12
RAAD-2
RAAD-24 (Mr. R.M. Ryan)
RM
RMMP-2
RMMP-11 (Mr. I. Silver)
RMMP-22 (Mr. J.C. Ardinger)
RR
RRRE
RRRE-61 (Mr. M.J. Marciniak)
RU
Department of the Navy
Washington, D. C. 20360

Chief, Bureau of Ships
Attn: Code 210-L
305
345
421
423
430
440
442
443
1500
Department of the Navy
Washington, D. C. 20360

Commander
U. S. Naval Weapons Laboratory
Dahlgren, Virginia 22448

Bureau of Yards & Docks Tech. Lib.
Yards & Docks Annex
Department of the Navy
Washington, D. C. 20390

Air Force

Commander, WADD
Attn: Code WWRMDD
AFFDL (FDDS)
Structures Division
AFLC (MCREA)
Code WWRMDS
AFFDL (FDT)
Code WWRC
AFML (MAAM)
Code WCLSY
SEG (SEPSD, Mr. Lakin)
Wright-Patterson Air Force Base
Dayton, Ohio 45433

Commander
Chief, Applied Mechanics Group
U. S. Air Force Inst. of Tech.
Wright-Patterson Air Force Base
Dayton, Ohio 45433

Chief, Civil Engineering Branch
WLRC, Research Division
Air Force Weapons Laboratory
Kirtland AFB, New Mexico 87117

Commander
AFRPL (RPRC/Dr. F.M. Kelley)
Edwards AFB, California 93523

Commander
Attn: Mr. A.L. Skinner, OCMSQC
Hill AFB, Utah 84401

Commander
Mechanics Division
Air Force Office of Scien. Res.
Washington, D. C. 20333

NASA

Structures Research Division
Attn: Mr. R. R. Heldenfels, Chief
National Aeronautics & Space Admin.
Langley Research Center
Langley Station
Hampton, Virginia 23365

Navy (cont'd.)

Undersea Explosion Research Div.
Attn: Mr. D. S. Cohen
Code 780
David Taylor Model Basin
Norfolk Naval Shipyard
Portsmouth, Virginia 23709

Commanding Officer & Director
Code 257, Library
U. S. Navy Marine Engr. Lab.
Annapolis, Maryland 21402

Commander
Technical Library
U. S. Naval Ordnance Test Station
Pasadena Annex
3202 E. Foothill Blvd.
Pasadena, California 91107

U. S. Naval Ordnance Test Station
Attn: Dr. Arnold Adicoff
Code 5056
China Lake, California 93557

Commander
U. S. Naval Ordnance Test Station
Mechanical Engineering Division
Code 556
China Lake, California 93557

Commanding Officer & Director
U. S. Naval Civil Engr. Lab.
Code L31
Port Hueneme, California 93041

Shipyard Technical Library
Code 242L
Portsmouth Naval Shipyard
Portsmouth, New Hampshire 03804

U. S. Naval Electronics Laboratory
Attn: Dr. R. J. Christensen
San Diego, California 92152

U. S. Naval Ordnance Laboratory
Mechanics Division
NOL 1, White Oak
Silver Spring, Maryland 20910

U. S. Naval Ordnance Laboratory
Attn: Mr. H. A. Perry, Jr.
Non-Metallic Materials Division
Silver Spring, Maryland 20910

Supervisor of Shipbuilding
U. S. Navy
Newport News, Virginia 23607

Shipyard Technical Library
Building 746, Code 303TL
Mare Island Naval Shipyard
Vallejo, California 94592

Director
U.S. Navy Underwater Sound Ref. Lab.
Office of Naval Research
P. O. Box 8337
Orlando, Florida 32806

Technical Library
U. S. Naval Propellant Plant
Indian Head, Maryland 20640

U. S. Naval Propellant Plant
Attn: Dr. J. O. Tsono
Research & Development Division
Indian Head, Maryland 20640

Chief of Naval Operations
Attn: Code Op-03EG
Op-07T
Department of the Navy
Washington, D. C. 20350

Director, Special Projects
Attn: Sp-001
43
2731
Department of the Navy
Washington, D. C. 20360

Executive Secretary PLRB
Special Projects Office (Sp-00110)
Department of the Navy
Washington, D. C. 20360

U. S. Naval Applied Science Lab.
Code 9832
Technical Library
Building 291, Naval Base
Brooklyn, New York 11251

Director
Aeronautical Materials Lab.
Naval Air Engineering Center
Naval Base
Philadelphia, Pennsylvania 19112

NASA (cont'd.)

National Aeronautics & Space Admin.
Code RV-2
Washington, D. C. 20546

National Aeronautics & Space Admin.
Associate Administrator for Advanced
Research & Technology
Washington, D. C. 20546

Scientific & Tech. Info. Facility
NASA Representative (S-AK/RL)
P. O. Box 5700
Bethesda, Maryland 20014

Other Government Activities

Commandant
Chief, Testing & Development Div.
U. S. Coast Guard
1300 E Street, N. W.
Washington, D. C. 20226

Director
Marine Corps Landing Force Devel. Cen.
Marine Corps Schools
Quantico, Virginia 22134

Director
Attn: Mr. B. L. Wilson
National Bureau of Standards
Washington, D. C. 20234

National Science Foundation
Engineering Division
1951 Constitution Avenue, N. W.
Washington, D. C. 20550

Science & Tech. Division
Library of Congress
Washington, D. C. 20540

Director
STBS
Defense Atomic Support Agency
Washington, D. C. 20301

Commander Field Command
Defense Atomic Support Agency
Sandia Base
Albuquerque, New Mexico 87115

Chief, Defense Atomic Support Agcy.
Blast & Shock Division
The Pentagon
Washington, D. C. 20301

Director Defense Research & Engr.
Technical Library
Room 3C-128
The Pentagon
Washington, D. C. 20301

Chief, Airframe & Equipment Branch
FS-120
Office of Flight Standards
Federal Aviation Agency
Washington, D. C. 20553

Chief, Division of Ship Design
Maritime Administration
Washington, D. C. 20235

Deputy Chief, Office of Ship Constr.
Attn: Mr. U. L. Russo
Maritime Administration
Washington, D. C. 20235

Executive Secretary
Committee on Undersea Warfare
National Academy of Sciences
2101 Constitution Avenue
Washington, D. C. 20418

Ship Hull Research Committee
Attn: Mr. A. R. Lytle
National Research Council
National Academy of Sciences
2101 Constitution Avenue
Washington, D. C. 20418

PART II - CONTRACTORS AND OTHER
TECHNICAL COLLABORATORS

Universities

Dr. D. C. Drucker
Division of Engineering
Brown University
Providence, Rhode Island 02912

Universities (cont'd)

Prof. M. E. Gurtin
Brown University
Providence, Rhode Island 02912

Prof. R. S. Rivlin
Division of Applied Mathematics
Brown University
Providence, Rhode Island 02912

Prof. P. J. Blatz
Materials Science Department
California Institute of Technology
Pasadena, California 91109

Prof. Julius Miklowitz
Div. of Engr. & Applied Sciences
California Institute of Technology
Pasadena, California 91109

Prof. George Sih
Department of Mechanics
Lehigh University
Bethlehem, Pennsylvania 18015

Solid Propellant Library
Firestone Flight Science Lab.
California Institute of Technology
Pasadena, California 91109

Prof. Eli Sternberg
Div. ofEngr. & Applied Sciences
California Institute of Technology
Pasadena, California 91109

Prof. Paul M. Naghdi
Div. of Applied Mechanics
Etcheverry Hall
University of California
Berkeley, California 94720

Prof. J. Baltrukonis
Mechanics Division
The Catholic Univ. of America
Washington, D. C. 20017

Prof. A. J. Durelli
Mechanics Division
The Catholic Univ. of America
Washington, D. C. 20017

Prof. H. H. Bleich
Departmentof Civil Engr.
Columbia University
Amsterdam & 120th Street
New York, New York 10027

Prof. R. D. Mindlin
Department of Civil Engr.
Columbia University
S. W. Mudd Building
New York, New York 10027

Prof. B. A. Boley
Department of Civil Engr.
Columbia University
Amsterdam & 120th Street
New York, New York 10027

Prof. F. L. DiMaggio
Department of Civil Engr.
Columbia University
616 Mudd Building
New York, New York 10027

Prof. A. M. Freudenthal
Dept. of Civil Engr. & Engr. M
Columbia University
New York, New York 10027

Prof. William A. Nash
Dept. of Engr. Mechanics
University of Florida
Gainesville, Florida 32603

Prof. B. Budiansky
Div. of Engr. & Applied Physics
Pierce Hall
Harvard University
Cambridge, Massachusetts 02138

Prof. P. G. Hodge
Department of Mechanics
Illinois Institute of Technology
Chicago, Illinois 60616

Universities (cont'd.)

Dr. S. L. Koh
School of Aero., Astro. & Engr. Sc.
Purdue University
Lafayette, Indiana 47907

Prof. D. Schapery
Purdue University
Lafayette, Indiana 47907

Prof. E. H. Lee
Div. of Engr. Mechanics
Stanford University
Stanford, California 94305

Dr. Nicholas J. Hoff
Dept. of Aero. & Astro.
Stanford University
Stanford, California 94305

Prof. J. N. Goodier
Div. of Engr. Mechanics
Stanford University
Stanford, California 94305

Prof. Markus Reiner
Technion R & D Foundation, Ltd.
Haifa, Israel

Prof. Tsuyoshi Hayashi
Department of Aeronautics
Faculty of Engineering
University of Tokyo
BUNKYO-KU
Tokyo, Japan

Prof. R. J. H. Bollard
Chairman, Aeronautical Engr. Dept.
207 Guggenheim Hall
University of Washington
Seattle, Washington 98105

Prof. Albert S. Kobayashi
Dept. of Mechanical Engr.
University of Washington
Seattle, Washington 98105

Officer-in-Charge
Post Graduate School for Naval Off.
Webb Institute of Naval Arch.
Crescent Beach Road, Glen Cove
Long Island, New York 11542

Industry and Research Institutes

Mr. K. W. Bills, Jr.
Dept. 4722, Bldg. 0525
Aerojet-General Corporation
P. O. Box 1947
Sacramento, California 95809

Dr. James H. Wiegand
Senior Dept. 4720, Bldg. 0525
Ballistics & Mech. Properties Lab.
Aerojet-General Corporation
P. O. Box 1947
Sacramento, California 95809

Dr. John Zickel
Dept. 4650, Bldg. 0227
Aerojet-General Corporation
P. O. Box 1947
Sacramento, California 95809

Mr. J. S. Wise
Aerospace Corporation
P. O. Box 1308
San Bernardino, California 92402

Dr. Vito Salerno
Applied Technology Assoc., Inc.
29 Church Street
Ramsey, New Jersey 07446

Library Services Department
Report Section, Bldg. 14-14
Argonne National Laboratory
9700 S. Cass Avenue
Argonne, Illinois 60440

Dr. E. M. Kerwin
Bolt, Beranek, & Newman, Inc.
50 Moulton Street
Cambridge, Massachusetts 02138

Dr. M. C. Junger
Cambridge Acoustical Associates
129 Mount Auburn Street
Cambridge, Massachusetts 02138

Dr. F. R. Schwarzl
Central Laboratory T.N.O.
134 Julianalaan
Delft, Holland

Universities (cont'd)

Prof. H. T. Corten
University of Illinois
Urbana, Illinois 61803

Prof. W. J. Hall
Department of Civil Engr.
University of Illinois
Urbana, Illinois 61803

Prof. N. M. Newmark
Dept. of Civil Engineering
University of Illinois
Urbana, Illinois 61803

Dr. W. H. Avery
Applied Physics Laboratory
Johns Hopkins University
8621 Georgia Avenue
Silver Spring, Maryland 20910

Prof. J. B. Tiedemann
Dept. of Aero. Engr. & Arch.
University of Kansas
Lawrence, Kansas 66045

Prof. S. Taira
Department of Engineering
Kyoto University
Kyoto, Japan

Prof. E. Reissner
Dept. of Mathematics
Massachusetts Inst. of Tech.
Cambridge, Massachusetts 02139

Library (Code 0384)
U. S. Naval Postgraduate School
Monterey, California 93940

Dr. Joseph Marin
Prof. of Materials Science
Dept. of Materials Sc. & Chem.
U. S. Naval Postgraduate School
Monterey, California 93940

Prof. E. L. Reiss
Courant Inst. of Math. Sciences
New York University
4 Washington Place
New York, New York 10003

Dr. Francis Cozzarelli
Div. of Interdisciplinary
Studies and Research
School of Engineering
State Univ. of N.Y. at Buffalo
Buffalo, New York 14214

Dr. George Herrmann
The Technological Institute
Northwestern University
Evanston, Illinois 60201

Director, Ordnance Research Lab.
The Pennsylvania State University
P. O. Box 30
State College, Pennsylvania 16801

Prof. Eugen J. Skudrzyk
Department of Physics
Ordnance Research Lab.
The Pennsylvania State University
P. O. Box 30
State College, Pennsylvania 16801

Dean Oscar Baguio
Assoc. of Structural Engr.
of the Philippines
University of Philippines
Manila, Philippines

Prof. J. Kempner
Dept. of Aero. Engr. & Applied Mech.
Polytechnic Institute of Brooklyn
333 Jay Street
Brooklyn, New York 11201

Prof. J. Klosner
Polytechnic Institute of Brooklyn
333 Jay Street
Brooklyn, New York 11201

Prof. F. R. Eirich
Polytechnic Institute of Brooklyn
333 Jay Street
Brooklyn, New York 11201

Prof. A. C. Eringen
School of Aero., Astro. & Engr. Sc.
Purdue University
Lafayette, Indiana 47907

Industry & Research Inst. (cont'd.)

Mr. Ronald D. Brown
Applied Physics Laboratory
Chemical Propulsion Agency
8621 Georgia Avenue
Silver Spring, Maryland 20910

Research and Development
Electric Boat Division
General Dynamics Corporation
Groton, Connecticut 06340

Supervisor of Shipbuilding, USN,
and Naval Insp. of Ordnance
Electric Boat Division
General Dynamics Corporation
Groton, Connecticut 06340

Dr. L. H. Chan
Basic Engineering
Electric Boat Division
General Dynamics Corporation
Groton, Connecticut 06340

Mr. Ross H. Petty
Technical Librarian
Allegany Ballistics Lab.
Hercules Powder Company
P. O. Box 210
Cumberland, Maryland 21501

Dr. J. H. Thacher
Allegany Ballistic Laboratory
Hercules Powder Company
Cumberland, Maryland 21501

Dr. Joshua E. Greenspon
J. G. Engr. Research Associates
3831 Menlo Drive
Baltimore, Maryland 21215

Mr. R. F. Landel
Jet Propulsion Laboratory
4800 Oak Grove Drive
Pasadena, California 91103

Ms. G. Lewis
Jet Propulsion Laboratory
4800 Oak Grove Drive
Pasadena, California 91103

Industry & Research Inst. (cont'd.)

Dr. R. C. DeHart
Southwest Research Institute
8500 Culebra Road
San Antonio, Texas 78206

Dr. Thor Smith
Stanford Research Institute
Menlo Park, California 94025

Mr. J. Edmund Fitzgerald
Director, Research & Engr.
Lockheed Propulsion Company
P. O. Box 111
Redlands, California 92374

Library
Newport News Shipbuilding &
Dry Dock Company
Newport News, Virginia 23607

Mr. E. A. Alexander
Rocketdyne Division
North American Aviation, Inc.
6633 Canoga Avenue
Canoga Park, California 91304

Mr. Cesar P. Muguid
Deputy Commissioner
Philippine Atomic Energy Commission
Manila, Philippines

Mr. S. C. Britton
Solid Rocket Division
Rocketdyne
P. O. Box 548
McGregor, Texas 76657

Dr. A. J. Ignatowski
Redstone Arsenal Research Div.
Rohm & Haas Company
Huntsville, Alabama 35807

Dr. M. L. Merritt
Division 5412
Sandia Corporation
Sandia Base
Albuquerque, New Mexico 87115

Director
Ship Research Institute
Ministry of Transportation
700, SHINKAWA
Mitake
Tokyo, JAPAN

Dr. H. W. Ahnemann
Southwest Research Institute
8500 Culebra Road
San Antonio, Texas 78206

Dr. M. L. Baron
Paul Weidlinger, Consulting Engr.
777 Third Ave. - 22nd Floor
New York, New York 10017

Unclassified
Security Classification

DOCUMENT CONTROL DATA - R&D

(Security classification of title, body of abstract and indexing annotation must be entered when the overall report is classified)

1. ORIGINATING ACTIVITY (Corporate author)	2a. REPORT SECURITY CLASSIFICATION
Department of Mechanics Lehigh University	Unclassified
	2b. GROUP

3. REPORT TITLE

Geometric Discontinuities in Elastostatics

4. DESCRIPTIVE NOTES *(Type of report and inclusive dates)*

Research Project

5. AUTHOR(S) *(Last name, first name, initial)*

Kaseir, M. K., and G. C. Sih

6. REPORT DATE	7a. TOTAL NO. OF PAGES	7b. NO. OF REFS
	28	10

8a. CONTRACT OR GRANT NO.	9a. ORIGINATOR'S REPORT NUMBER(S)
Nonr-610(06)	No. 3
b. PROJECT NO. NR-064-476	
c.	9b. OTHER REPORT NO(S) *(Any other numbers that may be assigned this report)*
d.	

10. AVAILABILITY/LIMITATION NOTICES

Reproduction in whole or in part is permitted by the United States Government. Distribution of this document is unlimited.

11. SUPPLEMENTARY NOTES	12. SPONSORING MILITARY ACTIVITY
	Office of Naval Research

13. ABSTRACT

Three-dimensional elastostatic problems for an infinite solid with geometric discontinuities are formulated and solved with the aid of potential functions. In the problem of a linearly varying pressure specified over a plane region bounded by an ellipse, use is made of the gravitational potential at an exterior point of a homogeneous elliptical disk. The problem of prescribing displacements on the surfaces of discontinuity is governed by the Newtonian potential of a simple layer distributed over a disk in the shape of the region of discontinuity. The mass density of the disk is proportional to the prescribed normal displacement. For an "elliptically shaped" region, the application of the symmetrical form of ellipsoidal coordinate leads to an integral equation of the Abel type for the potential function. It is shown that if the displacements normal to the elliptical plane are given by a polynomial in the variables x^2 and y^2, then the corresponding normal stress acting over the ellipse is also a polynomial. The results given in this report are useful in the prediction of the stability behavior of elastic solids containing geometric discontinuities.

DD FORM 1 JAN 64 1473

Unclassified
Security Classification

14. KEY WORDS	LINK A		LINK B		LINK C	
	ROLE	WT	ROLE	WT	ROLE	WT
Three-dimensional Elasticity						
Geometric Discontinuities						
Potential functions						
Ellipsoidal coordinates						

INSTRUCTIONS

1. ORIGINATING ACTIVITY: Enter the name and address of the contractor, subcontractor, grantee, Department of Defense activity or other organization *(corporate author)* issuing the report.

2a. REPORT SECURITY CLASSIFICATION: Enter the overall security classification of the report. Indicate whether "Restricted Data" is included. Marking is to be in accordance with appropriate security regulations.

2b. GROUP: Automatic downgrading is specified in DoD Directive 5200.10 and Armed Forces Industrial Manual. Enter the group number. Also, when applicable, show that optional markings have been used for Group 3 and Group 4 as authorized.

3. REPORT TITLE: Enter the complete report title in all capital letters. Titles in all cases should be unclassified. If a meaningful title cannot be selected without classification, show title classification in all capitals in parenthesis immediately following the title.

4. DESCRIPTIVE NOTES: If appropriate, enter the type of report, e.g., interim, progress, summary, annual, or final. Give the inclusive dates when a specific reporting period is covered.

5. AUTHOR(S): Enter the name(s) of author(s) as shown on or in the report. Enter last name, first name, middle initial. If military, show rank and branch of service. The name of the principal author is an absolute minimum requirement.

6. REPORT DATE: Enter the date of the report as day, month, year; or month, year. If more than one date appears on the report, use date of publication.

7a. TOTAL NUMBER OF PAGES: The total page count should follow normal pagination procedures, i.e., enter the number of pages containing information.

7b. NUMBER OF REFERENCES: Enter the total number of references cited in the report.

8a. CONTRACT OR GRANT NUMBER: If appropriate, enter the applicable number of the contract or grant under which the report was written.

8b, 8c, & 8d. PROJECT NUMBER: Enter the appropriate military department identification, such as project number, subproject number, system numbers, task number, etc.

9a. ORIGINATOR'S REPORT NUMBER(S): Enter the official report number by which the document will be identified and controlled by the originating activity. This number must be unique to this report.

9b. OTHER REPORT NUMBER(S): If the report has been assigned any other report numbers *(either by the originator or by the sponsor)*, also enter this number(s).

10. AVAILABILITY/LIMITATION NOTICES: Enter any limitations on further dissemination of the report, other than those imposed by security classification, using standard statements such as:

(1) "Qualified requesters may obtain copies of this report from DDC."

(2) "Foreign announcement and dissemination of this report by DDC is not authorized."

(3) "U. S. Government agencies may obtain copies of this report directly from DDC. Other qualified DDC users shall request through _____."

(4) "U. S. military agencies may obtain copies of this report directly from DDC. Other qualified users shall request through _____."

(5) "All distribution of this report is controlled. Qualified DDC users shall request through _____."

If the report has been furnished to the Office of Technical Services, Department of Commerce, for sale to the public, indicate this fact and enter the price, if known.

11. SUPPLEMENTARY NOTES: Use for additional explanatory notes.

12. SPONSORING MILITARY ACTIVITY: Enter the name of the departmental project office or laboratory sponsoring *(paying for)* the research and development. Include address.

13. ABSTRACT: Enter an abstract giving a brief and factual summary of the document indicative of the report, even though it may also appear elsewhere in the body of the technical report. If additional space is required, a continuation sheet shall be attached.

It is highly desirable that the abstract of classified reports be unclassified. Each paragraph of the abstract shall end with an indication of the military security classification of the information in the paragraph, represented as *(TS), (S), (C), or (U)*

There is no limitation on the length of the abstract. However, the suggested length is from 150 to 225 words.

14. KEY WORDS: Key words are technically meaningful terms or short phrases that characterize a report and may be used as index entries for cataloging the report. Key words must be selected so that no security classification is required. Identifiers, such as equipment model designation, trade name, military project code name, geographic location, may be used as key words but will be followed by an indication of technical context. The assignment of links, roles, and weights is optional.